

#### Indian Institute of Technology Kanpur STUDENTS' PLACEMENT OFFICE



Enquiry No. SPO/2015/1
Enquiry Date: Jan 24, 2015
Closing Date: Feb 03, 2015 (latest by 3:00 PM)
Delivery Date: 15 February 2015
Manch

Sub: Quotations invited for the following items.

# SI. No 1) EXECUTIVE CHAIR MEDIUM BACK - QTY 20

	Chair Dimensions	65 cm(W)X116cm(H)±1cm
Size	Seat Height	50cm(H) to 56.5cm(H) ±1cm
	Back Size	52cm(W)X70cm(H)±1cm
	Tubular Frame Diameter	Ø2.54cm
	Pedestal Diameter	Ø66cm
	Upholstered	Urethane foam with fabric upholstery
	Seat	1.2±0.2cm thick hot pressed ply.
<b>)</b> .	Foam Type Man 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Urethane foam.
Material	Foam Density	40±2kg/m3.
	Foam Hardness Load	N/A
	Arm rests	Silver Poly urethane arm rest.
	Twin Wheel Castors	Injection molded black nylon
	Base	Silver Poly urethane five legs
	Pneumatic height adjustment Stroke	6.5cm
	Locking	Upright locking.
	Revolution	360 degree
Pedestal	Type MA	Twin wheel castor shall be injection molded in black 33% glass filled nylon -66.
	No	5
e granda para	Bellow type	Metal with
	Contour Lumber Support	yes

Page 1 of 9

## SI. No. 2) EXECUTIVE CHAIR - QTY 2

	Chair Dimensions	65 cm(W)X116cm(H)±1cm
Size	Seat Height	50cm(H) to 56.5cm(H) ±1cm
	Back Size	52cm(W)X70cm(H)±1cm
	Head Rest	25x17.5cm
the time of the section at	Tubular Frame Diameter	Ø2.54cm
	Pedestal Diameter	Ø66cm
	Upholstered	Urethane foam with fabric upholstery
	Seat	1.2±0.2cm thick hot pressed ply.
	Foam Type	Urethane foam.
Material	Foam Density	40±2kg/m3.
	Foam Hardness Load	N/A confidences at tight to be a
	Arm rests	Poly urethane arm rest.
	Twin Wheel Castors	Injection molded black nylon
ANT HE WASTLAND BY	Seat/Back tilting ratio	1:2
	Pneumatic height adjustment Stroke	6.5cm
Adjustment	Locking	Upright four position locking.
	Revolution	360 degree
Pedestal	Туре	Twin wheel castor shall be injection molded in black 33% glass filled nylon -66.
	No galas a se para da A	5 - See State Stat
	Bellow type	Metal with
	Contour Lumber Support	yes

## SI. No. 3) STORAGE UNIT - QTY 1

	Dimensions Single unit	910 mm(W)X455mm(W)X2080mm(H)±20mm
Size	Dimension Double Unit	910 mm(W)X910mm(W)X2080mm(H)±20mm
	Steel Sheet	Cold Rolled
	Locking knob	Brass with chrome plating
	Handle	ABS
Material	Rail WA 1 1 /4	Solid steel
	Base Plate	Solid steel
	Pulley	Solid steel with chrome plating
	Chain	Machenical
	Body	Moon light
Colour	Cover of the Machines	Blue
	Handles	Black
Number	Single	One
	Double	Two
	Single with mobility	One



## Sl. No. 4) Conference table – QTY 1

	Overall Dimensions	2400x2400mm
Size	Dimension Unit 1	2400x600x750mm
ger en graga gare.	Dimension Unit 2	1200x600x750mm
	Dimension Unit 3	600x600mm
	Тор	25mm pre lam, Grade (IS:3087:1985)
		Thickness 18MM with 2MM thick PVC Edge
	Gable ends	18mm, Grade (IS:3087:1985)
Material		Thickness 18MM with 2MM thick PVC Edge
	Modesty West 19	18mm, Grade (IS:3087:1985)
		Thickness 18MM with 2MM thick PVC Edge
	Wire Manager	PVC 50mm
Number	2400x600x750	One
	1200x600x750mm	Two
	600x600x750mm	two

## SI. No. 5) EXECUTIVE TABLE - QTY 1

	Dimensions	2100x750x750MM
Size	Side runner	1200x400x750mm
	Back Storage	2400x450x2100mm
	Pedestal Diameter	Ø45mm
Material	Тор	Grade (IS:3087:1985)
		Thickness 25MM with 2MM thick PVC Edge
	Gable End	Grade (IS:3087:1985)
		Thickness 18MM with 2MM thick PVC Edge
	Modesty March 19	Grade (IS:3087:1985)
		Thickness 18MM with 2MM thick PVC Edge
	Pedestal	Ø45mm with Chrome Plated
	Hardware	Hattich/E bay/Hafle
Design	Тор	Bubble shaped
	Noof Pedestal	1
	Modesty	600mm

## Sl. No. 6) (i) Pantry Storage – QTY 1

Size	OVERALL HEIGHT	600MM
	OVERALL DEPTH	600MM
	OVERALL LENGTH	3225MM
Material	BASKETS	STAINLESS STEEL:
	VERTICLES	MARBLE THICKNESS 16MM
	SLIDING CHENELS	HETTICH FREEFLOW TELESCOPIC FULL LENGHT
	FRACIA	18MM PRELAM WITH 2MM THICK PVEC EDGE
	HANDLE	STAINLESS STEEL 'C' TYPE
DESIGN	-MULTI PER DRAWERS AND CUB BOARD AS PER APPROVED DESIGN, -LAMINATE DESIGN-AS APPROVED	

## Sl. No. 6) (ii) Modular Over Head Storage - QTY 1

SIZE	1800x400x600MM (L x D x H)	
Shelve	One shelve ,	
Post Michell Sect as were d	Horizontal	
Shutteres	Prelam frame with 6MM Glass	
Board	Grade (IS:3087:1985)	
	Thickness 18MM with 2MM thick PVC Edge	

## Sl. No. 7) Modular Over Head Storage for Office - QTY 8

Dimensions	1200mm (W) x450mm (D) x600mm (H)	
Shutters	Three lockable shutters with drawers SS handle	
Shelve	One shelve ,	
	Horizontal	
Board	Grade (IS:3087:1985)	
	Thickness 18MM with 2MM thick PVC Edge	
2.	solve a to the set of the set of the set	

# Sl. No. 8) Modular Table for Office – QTY 8

	Work Surface Dimensions	1200mm (W) x600mm (D) x 750mm (H)
* .	Work Top	25mm Thick Post Foamed& 2MM thick PVC Edge three sides
	Frame	Wall thickness 46mm or more
Size	e articulare contrata en engança capacidad equ	Height 1200MM
	Drawer Pedestals	450x550x600MM
	Board	Grade (IS:3087:1985)
	Partition	Prelam upto 750mm
Material	Adv	Each work surface shall be covered from three sides with 1200MM partition
tyr k doe ty styr (west) - we, west	ergymosphak kondindynospham an angestrick e	From work top to full height-Half Glass marker and rest Pin Up covered with Matte of approved colour
		Leveler adjuster
	Metal Sheet	1MM thick cold rolled with Powder coating  Mobile
	Power Port	4x5 amps (Universal Plug Adaptor
Power & Electric Ports	Network Port	2 x RJ-45
Design	Partition	46 MM Partition, with Powder coated casing and MS frame with Pre lam, Marker Glass & Pin Up Board
	Тор	25 MM of approved colour & design
	er e	One side Post form
		Three side 2MM thick PVC Edge
	Raceway	Two nos., One at the bottom and other below the top
	Drawer Pedestal	Mobile with two drawers and one filing, fitted with Hettich, Telescopicball bearing runner channels

Page 8 of 9

THE MENTAL SECTION OF	the second secon	single locking system,
	Key Board Trey	18MM thick with 2MM Thick PVC Edge fitted with telescopic ball bearing runner, hettich
	CPU Trolley	Metal with caster wheels and adjustable width

#### **Terms & condition:**

- 1. Quotations must be valid for 6 months.
- 2. After the work order the delivery period will be a maximum of two weeks. Vendor should note that order shall be placed in phased manner.
- 3. Warranty should be properly mentioned in the quotation.
- 4. Payment shall be made after delivery and satisfactory report from the user.
- 5. The rates and taxes, if any should be clearly specified.
- 6. The indenter reserves the right to withhold the work order and change the specification without any notice.
- 7. The quotation should reach to Chair SPC, 109 Outreach building, IIT Kanpur-208016 by 3 PM on 30<sup>th</sup> January, 2015.

(Dr. Deepu Philip) Chair, SPC